

ORION 2



900TXP-42



900TXB-42

900TXP-42

Deux canaux, code fixe. Gris foncé.
2-Kanäle, fix Code. Dunkel grau.

900TXB-42

Deux canaux, code fixe. Bleu transparent.
2-Kanäle, fix Code. Durchsichtig blau.

900TXP-42R

Deux canaux, rolling code. Gris foncé.
2-Kanäle, rolling Code. Dunkel grau.

900TXB-42R

Deux canaux, rolling code. Bleu transparent.
2-Kanäle, rolling Code. Durchsichtig blau.

900TXP-42N

Deux canaux. Gris foncé. Programmable.
2-Kanäle. Dunkel grau. Programmierbar.

ORION 2



900TXK-42R



900TXW-42R

900TXK-42R

Deux canaux, rolling code. Noir
2 kanäle, rolling code. Schwarz

900TXW-42R

Deux canaux, rolling code. Blanc
2 kanäle, rolling code. Weiß



900TXP-42R



900TXB-42R



900TXP-42N

DONNEES TECHNIQUES / TECHNISCHE DATEN

TXP-42 / TXB-42 / TXP-42R / TXB-42R / TXP-42N / TXK-42R / TXW-42R

fréquence d'émission / Sendefrequenz	433.920MHz
modulation / Modulation	on-off
tension piles / Batteriespannung	12V
consommation / Standardverbrauch	9Ma
consommation en stand-by / Stand-by Verbrauch	0,4µA
dimensions en mm. / Massen in mm	50x36x13
portée / Reichweite	50 / 150M

